




MeiG-SLM5 0P

Smart LTE

Wi-Fi & BT

3 P	UIS7863	2	8	2*A75@2.0GHz
+ 6*A55@1.8GHz		6		
Android 14	2	16	3	32
				150
3 P	3 P	3 P M	3 P EU	P
3 P				P

2*A75@2.0GHz + 6*A55@1.8GHz



150

F

2 x

24 @30fps ZSL

6

SLM530 -C:

LTE FDD: B1/B3/B5/B8

LTE TDD: B34/B38/B39/B40/B41(120M)

WCDMA: B1/B8

GSM: 900/1800MHz

EMEA/ / / / /

SLM530 -EM:

LTE FDD: B1/B2/B3/B4/B5/B7/B8/B20/B28

LTE TDD: B38/B40/B41(196M)

WCDMA: B1/B2/B4/B5/B8

GSM: 850/900/1800/1900MHz

SLM530 -AU:

LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28

LTE TDD: B38

WCDMA: B1/B2/B4/B5/B8

GSM: 850/900/1800/1900MHz

EMEA/ / / / /

SLM530 -EU:

LTE FDD: B1/B3/B5/B7/B8/B20/B28

LTE TDD: B38/B40/B41

WCDMA: B1/B5/B8

GSM: 900/1800MHz

SNM530

Wi-Fi & BT

LTE:

Cat 4 FDD 150Mbps (DL)/50Mbps (UL)

Cat 4 TDD 117Mbps (DL)/30Mbps(UL)

UMTS: DC-USDPA: 42Mbps(DL)

HSUPA: 5.76Mbps (UL)

WCDMA: 384Kbps (DL/UL)

GSM:

GPRS: 最大 107Kbps (DL)/85.6Kbps (UL)

EDGE: 最大 236.8Kbps (DL)/236.8Kbps (UL)

3. V~4. V

3.8V

Class 4 (33dBm±2dB) for GSM850

Class 4 (33dBm±2dB) for EGSM900

Class 1 (30dBm±2dB) for DCS1800

Class 1 (30dBm±2dB) for PCS1900

Class E2 (27dBm±3dB) for GSM850 8-PSK

Class E2 (27dBm±3dB) for EGSM900 8-PSK

Class E2 (26dBm±3dB) for DCS1800 8-PSK

Class E2 (26dBm±3dB) for PCS1900 8-PSK

Class 3 (24dBm+1/-3dB) for WCDMA bands

Class 3 (23dBm±2dB) for LTE-FDD bands

Class 3 (23dBm±2dB) for LTE-TDD bands

LTE FDD B1: -102dBm LTE FDD B3: -102dBm

LTE FDD B5: -102dBm LTE FDD B8: -102dBm

LTE TDD B34: -101dBm LTE TDD B38: -102dBm

LTE TDD B39: -102dBm LTE TDD B40: -102dBm

LTE TDD B41: -102dBm WCDMA B1: -110dBm

WCDMA B8: -110dBm

EGSM900: -109dBm

DCS1800: -109dBm

&

VoLTE

SRVCC/

CSFB

24-bit/192kHz

1080P@60fps

Wi-Fi

1080P@60fps

4-lane MIPI_DSI FHD+@60fps

x 4-lane + 1 x 1-lane MIPI_CSI; x ISP

24MP@30fps

16+8MP

16+8+2MP

USB

1 x USB 2.0

USB OTG 2.0

I2C

8

(U)SIM

2

1.8V/2.95V

UART

SD

1

SD 3.0, 4-bit SDIO

PWRKEY

SPI

3

GPIO

*

1

LED

1

GNSS

Wi-Fi & BT

WLAN 2.4G/5G, 802.11 a/b/g/n/ac

BT2.1+EDR/3.0/4.1 LE/4.2 BLE BT5.0

GNSS GPS/GLONASS/BeiDou

LTE Cat 4

L+L DSDS

USB

Android

GB eMMC+ GB LPDDR4x()()

GB eMMC+ GB LPDDR4x()()

分离式 可选

-30°C ~ +75°C

-40°C ~ +85°C

31 V~4.1V 0.~ [D4"Š F,i[ÄÄ %88 Öy 8 6 % €Q_6"